

Supplementary Instruction Sheet

WOOD KOTE PRODUCTS INC

Differences between original Jel'd Stain, Jel'd Stain 250 and Liqwid Stain 250

	Jel'd Stain (original)	Jel'd Stain 250	Liqwid Stain 250
Container	Available in 12-fl oz (335ml) and 32-fl oz (946ml) metal containers.	Available in 12-fl oz (335ml), 32-fl oz (946ml), 1-Gal (3,8L) and 5-Gal (19L) metal containers.	Available in 32-fl oz (946ml), 1-Gal (3,8L) and 5-Gal (19L) metal containers.
Colors	Available in 26 colors.	Same 26 colors as Jel'd Stain.	Same 26 colors as Jel'd Stain and Jel'd Stain 250.
VOC	Does not comply with the US Environmental Protection Agency (EPA) Volatile Organic Compound (VOC) emission requirements for Architectural and Industrial Maintenance coatings (effective 13Sep99) or with California SCAQMD Rule 1113 (effective 03June11).	Complies with the US Environmental Protection Agency (EPA) Volatile Organic Compound (VOC) emission requirements for Architectural and Industrial Maintenance coatings (effective 13Sep99) and with California SCAQMD Rule 1113 (effective 03June11).	Complies with the US Environmental Protection Agency (EPA) Volatile Organic Compound (VOC) emission requirements for Architectural and Industrial Maintenance coatings (effective 13Sep99) and with California SCAQMD Rule 1113 (effective 03June11).
Adhesion	Not recommended for floors.	Better adhesion under polyurethane, but not recommended for floors.	Recommended for floors because it has best adhesion under polyurethane.
Application	Can be applied with a cloth.	Can be applied with a cloth.	Can be applied with a cloth, pad, brush or sprayer.