

M A T E R I A L   S A F E T Y   D A T A   S H E E T

KORRECT-0 BRIGHT RED

PAGE: 1

PRODUCT NAME: KORRECT-O BRIGHT RED  
PRODUCT CODE: 0550

HMIS CODES: H F R P  
2 2 0 H

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: WOOD KOTE PRODUCTS INC.  
ADDRESS : 8000 NE 14TH PLACE  
PORTLAND, OR 97211

EMERGENCY PHONE : (800) 535-5053      DATE PRINTED : 10/01/10  
INFORMATION PHONE : (503) 285-8371      NAME OF PREPARER : C. JENKINS

===== SECTION II - COMPOSITION/ INFORMATION ON INGREDIENTS=====

2-METHOXY-1-METHYLETHYL ACETATE  
CAS-NO. 108-65-6 PERCENT (WT./ WT.) 30 - 60 %  
NJTSR NO.56705700001-5384P  
CAS-NO. TRADE SECRET PERCENT (WT./ WT.) 1 - 5 %  
ETHYLBENZENE  
CAS NO. 100-41-4 PERCENT (WT./ WT.) 0.1 - 1 %  
XYLENE  
CAS NO. 1330-20-7 PERCENT (WT./ WT.) 0.1 - 1 %

OTHER INFORMATION  
THIS MATERIAL IS CLASSIFIED AS HAZARDOUS UNDER OSHA REGULATIONS.

===== SECTION III - HAZARDS IDENTIFICATION =====

\*\*\* EMERGENCY OVERVIEW \*\*\*

FORM-PASTE COLOR RED    ODOR-SWEET ETHER-LIKE ODOR.  
MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.  
COMBUSTIBLE LIQUID AND VAPOR.

POTENTIAL HEALTH EFFECTS

EYE CONTACT

IRRITATING. MAY CAUSE TEARING, REDDENING AND/OR SWELLING.  
MAY CAUSE CONJUNCTIVITIS. MAY INJURE EYE TISSUE IF NOT REMOVED PROMPTLY.

SKIN CONTACT

A MODERATE SKIN IRRITANT BASED ON TESTING OF SIMILAR CHROMA CHEM BASE MIXTURES.  
PROLONGED OR REPEATED CONTACT MAY CAUSE IRRITATION.  
PROLONGED SKIN CONTACT WITH LARGE AMOUNTS OF ETHER ACETATES MAY CAUSE DROWSINESS.

INHALATION

POSSIBLY IRRITATING.  
EXCESSIVE INHALATION OF SOLVENT VAPORS MAY CAUSE NASAL AND RESPIRATORY IRRITATION  
AND CENTRAL NERVOUS SYSTEM EFFECTS INCLUDING DIZZINESS, WEAKNESS, FATIGUE,  
NAUSEA, HEADACHE, POSSIBLE UNCONSCIOUSNESS AND EVEN DEATH.

INGESTION

MAY CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, AND DIARRHEA.

**CHRONIC HEALTH HAZARD**

HIGH VAPOR CONCENTRATIONS (3000 PPM) OF PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE CAUSED UPPER RESPIRATORY IRRITATION AND LIVER AND KIDNEY EFFECTS IN SUBCHRONIC ANIMAL TESTING. THE RELEVANCE OF THESE RESULTS TO HUMANS IS NOT KNOWN. SUPPLIERS OF XYLENE HAVE REPORTED THAT HIGH LEVELS OF EXPOSURE TO XYLENE IN SOME ANIMAL STUDIES WERE REPORTED TO HAVE AFFECTED THE DEVELOPMENT OF THE EMBRYO/FETUS. THESE EFFECTS WERE OFTEN AT LEVELS WHICH ARE TOXIC TO THE MOTHER. THE SIGNIFICANCE OF THESE FINDINGS TO HUMAN EXPOSURE HAS NOT BEEN DETERMINED, PARTICULARLY THE EXPOSURE TO THE LOW LEVELS OF XYLENE FOUND IN THIS PRODUCT.

===== SECTION IV - FIRST AID MEASURES =====

**INHALATION**

IF INHALED, REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, GIVE OXYGEN. IF UNCONSCIOUS, EVALUATE THE NEED FOR ARTIFICIAL RESPIRATION. GET IMMEDIATE MEDICAL ATTENTION.

**SKIN CONTACT**

IMMEDIATELY FLUSH SKIN WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES WHILE REMOVING CONTAMINATED CLOTHING AND SHOES. THOROUGHLY WASH CLOTHING, SHOES AND PROTECTIVE EQUIPMENT BEFORE REUSE OR DISCARD. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSISTS.

**EYE CONTACT**

IN CASE OF CONTACT, IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 30 MINUTES, WHILE HOLDING EYELIDS APART. DO NOT ALLOW CONTAMINATED WATER TO CONTACT THE UNAFFECTED EYE OR FACE DURING IRRIGATION OF AN AFFECTED EYE. OBTAIN MEDICAL ATTENTION IMMEDIATELY.

**INGESTION**

DO NOT INDUCE VOMITING. IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO THE LUNGS. GET MEDICAL ATTENTION. IF THE HEART HAS STOPPED OR BREATHING HAS STOPPED, TRAINED PERSONNEL SHOULD BEGIN CARDIOPULMONARY RESUSCITATION OR ARTIFICIAL RESPIRATION IMMEDIATELY.

===== SECTION V - FIRE FIGHTING MEASURES =====

**FLASH POINT** 46.67 °C , 116 °F

**METHOD:** SETAFLASH CLOSED CUP

**OSHA FLAMMABILITY CLASSIFICATION** COMBUSTIBLE LIQUID

**SUITABLE EXTINGUISHING MEDIA:**

USE WATER SPRAY OR FOG, FOAM, DRY CHEMICAL OR CO2.

**SPECIFIC HAZARDS DURING FIRE FIGHTING**

COMBUSTIBLE LIQUID. VAPORS CAN TRAVEL TO A SOURCE OF IGNITION AND FLASH BACK. EXPLOSIVE MIXTURES MAY OCCUR AT TEMPERATURES AT OR ABOVE THE FLASHPOINT.

**FURTHER INFORMATION**

AS IN ANY FIRE, WEAR SELF-CONTAINED POSITIVE-PRESSURE BREATHING APPARATUS, (MSHA/NIOSH APPROVED OR EQUIVALENT) AND FULL PROTECTIVE GEAR. CONTAINERS CAN BUILD UP PRESSURE IF EXPOSED TO HEAT (FIRE). COOL WITH WATER SPRAY.

**===== SECTION VI - ACCIDENTAL RELEASE MEASURES =====**

**ADDITIONAL ADVICE**

ABSORB SPILL WITH INERT MATERIAL, THEN PLACE IN A CHEMICAL WASTE CONTAINER. AFTER REMOVAL, FLUSH CONTAMINATED AREA WITH WATER AND COLLECT FOR DISPOSAL. CLEAN UP SPILLS IMMEDIATELY. REMOVE SOURCES OF IGNITION AND VENTILATE AREA. USE A RESPIRATOR AND OTHER PROTECTIVE EQUIPMENT AS OUTLINED IN SECTION 8. OBEY RELEVANT LOCAL, STATE, PROVINCIAL AND FEDERAL LAWS AND REGULATIONS. DO NOT CONTAMINATE ANY LAKES, STREAMS, PONDS, GROUNDWATER OR SOIL.

**===== SECTION VII - HANDLING AND STORAGE =====**

**SAFE HANDLING ADVICE**

KEEP AWAY FROM HEAT. KEEP AWAY FROM SPARKS, FLAMES AND OTHER SOURCES OF IGNITION. AVOID CONTACT WITH EYES, SKIN AND CLOTHING. AVOID BREATHING VAPOR OR MIST. USE WITH ADEQUATE VENTILATION. THE NEED FOR GROUNDING AND BONDING OF CONTAINERS IN ACCORDANCE WITH OSHA 29 CFR 1910.106 AND NFPA 77 SHOULD BE ASSESSED FOR ALL PRODUCT TRANSFERS. FOLLOW ALL MSDS/LABEL PRECAUTIONS EVEN AFTER THE CONTAINER IS EMPTIED BECAUSE IT MAY RETAIN PRODUCT RESIDUES. WASH THOROUGHLY AFTER HANDLING.

**STORAGE**

REQUIREMENTS FOR STORAGE AREAS AND CONTAINERS KEEP IN A DRY, COOL PLACE. KEEP CONTAINER CLOSED WHEN NOT IN USE. RESIDUAL VAPORS MIGHT EXPLODE ON IGNITION; DO NOT APPLY HEAT, CUT, DRILL, GRIND OR WELD ON OR NEAR THIS CONTAINER.

**===== SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION =====**

**COMPONENT OCCUPATIONAL EXPOSURE GUIDELINES**

**ETHYLBENZENE**

CAS NO. 100-41-4

100 PPM TIME WEIGHTED AVERAGE (TWA):(ACGIH) PEL(OSHA Z1)

435 MG/M3 TIME WEIGHTED AVERAGE (TWA):(ACGIH) PEL(OSHA Z1)

125 PPM STEL (ACGIH) (US CA OEL)

**XYLENE**

CAS NO. 1330-20-7

100 PPM TIME WEIGHTED AVERAGE (TWA):(ACGIH) PEL(OSHA Z1)

435 MG/M3 TIME WEIGHTED AVERAGE (TWA):(ACGIH) PEL(OSHA Z1)

125 PPM STEL (ACGIH) (US CA OEL)

300 PPM CEILING LIMIT VALUE (US CA OEL)

**OTHER INFORMATION**

EXPOSURE VALUES FOR MINERAL SPIRITS (CAS# 8052-41-3) ARE GIVEN AS STODDARD SOLVENT. THE AIHA WHEEL FOR PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE IS 50 PPM TWA.

**ENGINEERING MEASURES**

USE EXPLOSION-PROOF VENTILATION EQUIPMENT.

**PERSONAL PROTECTIVE EQUIPMENT**

**RESPIRATORY PROTECTION**

A RESPIRATORY PROTECTION PROGRAM THAT MEETS OSHA 1910.134 AND ANSI Z88.2 OR APPLICABLE FEDERAL/PROVINCIAL REQUIREMENTS MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT RESPIRATOR USE. NIOSH'S "RESPIRATOR DECISION LOGIC" MAY BE USEFUL IN DETERMINING THE SUITABILITY OF VARIOUS TYPES OF RESPIRATORS.

**HAND PROTECTION**

USE IMPERMEABLE GLOVES.

**EYE PROTECTION**

CHEMICAL RESISTANT GOGGLES MUST BE WORN.

**SKIN AND BODY PROTECTION**

A SAFETY SHOWER AND EYE WASH FOUNTAIN SHOULD BE READILY AVAILABLE. TO IDENTIFY ADDITIONAL PERSONAL PROTECTIVE EQUIPMENT (PPE) REQUIREMENTS, IT IS RECOMMENDED THAT A HAZARD ASSESSMENT IN ACCORDANCE WITH THE OSHA PPE STANDARD (29CFR1910.132) BE CONDUCTED BEFORE USING THIS PRODUCT.

===== SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES =====

FORM PASTE

COLOR RED

ODOR SWEET ETHER-LIKE ODOR.

**SAFETY DATA**

BOILING POINT/RANGE > 143 °C

FLASH POINT 46.67 °C

METHOD: SETAFLASH CLOSED CUP

RELATIVE DENSITY 1.1 (25 °C)

SOLUBILITY/QUALITATIVE SOLUBILITY IN WATER: NEGLIGIBLE.

VISCOSITY, DYNAMIC 80 - 95 KU (25 °C)

**SOLVENTS AND VOLATILES DATA**

% VOC (GM/L) 617.74

EVAPORATION RATE SLOWER THAN BUTYL ACETATE

===== SECTION X - STABILITY AND REACTIVITY =====

CONDITIONS TO AVOID: AVOID HIGH TEMPERATURES AND SOURCES OF IGNITION.

MATERIALS TO AVOID: OXIDIZING SUBSTANCES

===== SECTION XI - TOXICOLOGICAL INFORMATION =====

**COMPONENT ACUTE ORAL TOXICITY**

2-METHOXY-1-METHYLETHYL ACETATE

108-65-6

LD50 RAT: 8532 MG/KG

NJTSR NO.56705700001-5384P

TRADE SECRET

LD50 RAT: > 10000 MG/KG

ETHYLBENZENE

100-41-4

LD50 RAT: 3500 MG/KG

XYLENE

1330-20-7

LD50 RAT: 3523 MG/KG

KORRECT-0 BRIGHT RED

PAGE: 5

**COMPONENT ACUTE DERMAL TOXICITY**

2-METHOXY-1-METHYLETHYL ACETATE

108-65-6

LD50 RABBIT: > 19000 MG/KG

(CALCULATED)

(LITERATURE VALUE)

NJTSR NO.56705700001-5384P

TRADE SECRET

LD50 RABBIT: > 3000 MG/KG

ETHYLBENZENE

100-41-4

LD50 RABBIT: >5000 MG/KG

XYLENE

1330-20-7

LD50 RABBIT: >4300 MG/KG

**COMPONENT CARCINOGENICITY ASSESSMENT**

ETHYLBENZENE

100-41-4

CONTAINS A COMPONENT WHICH IS CLASSIFIED AS AN IARC 2B CARCINOGEN (POSSIBLY CARCINOGENIC TO HUMANS).

**COMPONENT TERATOGENICITY**

XYLENE

1330-20-7

INHALATIVE RAT: IN MATERNALLY NON-TOXIC DOSES.

SUPPLIERS OF XYLENE HAVE REPORTED THAT HIGH LEVELS OF EXPOSURE TO XYLENE IN SOME ANIMAL STUDIES WERE REPORTED TO HAVE AFFECTED THE DEVELOPMENT OF THE EMBRYO/FETUS. THESE EFFECTS WERE OFTEN AT LEVELS WHICH ARE TOXIC TO THE MOTHER. THE SIGNIFICANCE OF THESE FINDINGS TO HUMAN EXPOSURE HAS NOT BEEN DETERMINED, PARTICULARLY THE EXPOSURE TO THE LOW LEVELS OF XYLENE FOUND IN THIS PRODUCT.

**COMPONENT TERATOGENICITY ASSESSMENT**

XYLENE

1330-20-7

POTENTIAL EMBRYO-FOETAL TOXICITY AND TERATOGENICITY.

**COMPONENT GENERAL TOXICITY INFORMATION**

2-METHOXY-1-METHYLETHYL ACETATE

108-65-6

HIGH VAPOR CONCENTRATIONS (3000 PPM) OF PROPYLENE GLYCOL MONOMETHYL

ETHER ACETATE CAUSED UPPER RESPIRATORY IRRITATION AND LIVER AND KIDNEY EFFECTS IN SUBCHRONIC ANIMAL TESTING. THE RELEVANCE OF THESE RESULTS TO HUMANS IS NOT KNOWN.

===== SECTION XII - ECOLOGICAL INFORMATION =====

GENERAL ECOLOGICAL INFORMATION NO ECOTOXICOLOGICAL STUDIES ARE AVAILABLE.

===== SECTION XIII - DISPOSAL CONSIDERATIONS =====

**WASTE DISPOSAL**

ADVICE ON DISPOSAL WASTE MUST BE DISPOSED OF IN ACCORDANCE WITH FEDERAL, STATE, PROVINCIAL AND LOCAL REGULATIONS. CONTAINER DISPOSAL: EMPTY CONTAINERS BY REMOVING THE TOP AND INVERTING TO ALLOW ALL FREE FLOWING PRODUCT TO DRAIN. TO MEET REGULATORY CRITERIA, THE CONTAINER IS CONSIDERED EMPTY WHEN LESS THAN 3% REMAINS IN THE CONTAINER. ADDITIONAL SPECIAL HANDLING IS NOT TYPICALLY REQUIRED AND THE EMPTY CONTAINER CAN BE DISCARDED WITH OTHER NONHAZARDOUS TRASH. NOTE: LOCAL DISPOSAL REGULATIONS MAY BE MORE STRINGENT AND REQUIRE ADDITIONAL RESTRICTIONS OR PRECAUTIONS. CUSTOMERS SHOULD CHECK WITH THEIR LOCAL DISPOSAL COMPANY, MUNICIPAL OR STATE AUTHORITY. RECYCLE OF PLASTIC OR METAL CONTAINERS MAY REQUIRE CLEAN RATHER THAN EMPTY CONTAINERS. IN THIS CASE THE CONTAINERS CAN BE RINSED WITH MINERAL SPIRITS UNTIL THE CONTAINERS ARE CONSIDERED GENERALLY PRODUCT FREE.

===== SECTION XIV - TRANSPORT INFORMATION =====

SEA TRANSPORT IMDG-CODE

CLASS 3  
 UN-NO 1263  
 PACKAGING GROUP III  
 EMS F-E, S-E  
 PROPER TECHNICAL NAME (PROPER SHIPPING NAME)  
 PAINT RELATED MATERIAL  
 AIR TRANSPORT ICAO-TI/IATA-DGR

CLASS 3  
 UN-NO 1263  
 PACKAGING GROUP III  
 PROPER TECHNICAL NAME (PROPER SHIPPING NAME)  
 PAINT RELATED MATERIAL  
 LOADING INSTRUCTIONS/REMARKS  
 IATA\_C ERG-CODE 3L  
 IATA\_P ERG-CODE 3L

CFR\_INWTR IN THE U.S. THIS MATERIAL MAY BE CLASSIFIED AS COMBUSTIBLE LIQUID. COMBUSTIBLE LIQUIDS ARE NOT REGULATED IN PACKAGES 450 LITERS OR LESS. THIS APPLIES FOR SHIPMENTS BY ROAD AND RAIL ONLY.  
 CFR\_RAIL IN THE U.S. THIS MATERIAL MAY BE CLASSIFIED AS COMBUSTIBLE LIQUID. COMBUSTIBLE LIQUIDS ARE NOT REGULATED IN PACKAGES 450 LITERS OR LESS. THIS APPLIES FOR SHIPMENTS BY ROAD AND RAIL ONLY.  
 CFR\_ROAD IN THE U.S. THIS MATERIAL MAY BE CLASSIFIED AS COMBUSTIBLE LIQUID. COMBUSTIBLE LIQUIDS ARE NOT REGULATED IN PACKAGES 450 LITERS OR LESS. THIS APPLIES FOR SHIPMENTS BY ROAD AND RAIL ONLY.

===== SECTION XV - REGULATORY INFORMATION =====

**US FEDERAL REGULATIONS**

**OSHA**

IF LISTED BELOW, CHEMICAL SPECIFIC STANDARDS APPLY TO THE PRODUCT OR COMPONENTS:

- NONE LISTED

**CLEAN AIR ACT SECTION (112)**

IF LISTED BELOW, COMPONENTS PRESENT AT OR ABOVE THE DE MINIMUS LEVEL ARE HAZARDOUS AIR POLLUTANTS:

- NONE LISTED

**CERCLA REPORTABLE QUANTITIES**

IF LISTED BELOW, A REPORTABLE QUANTITY (RQ) APPLIES TO THE PRODUCT BASED ON THE PERCENT OF THE NAMED COMPONENT:

- NONE LISTED

**SARA TITLE III SECTION 311/312 HAZARD CATEGORIES**

THE PRODUCT MEETS THE CRITERIA ONLY FOR THE LISTED HAZARD CLASSES:

- ACUTE HEALTH HAZARD
- CHRONIC HEALTH HAZARD
- FIRE HAZARD

**SARA TITLE III SECTION 313 REPORTABLE SUBSTANCES**

IF LISTED BELOW, COMPONENTS ARE SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE

**SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:**

- NONE LISTED

**TOXIC SUBSTANCES CONTROL ACT (TSCA)**

IF LISTED BELOW, NON-PROPRIETARY SUBSTANCES ARE SUBJECT TO EXPORT NOTIFICATION UNDER SECTION 12 (B) OF

**TSCA:**

- NONE LISTED

STATE REGULATIONS

**CALIFORNIA PROPOSITION 65**

A WARNING UNDER THE CALIFORNIA DRINKING WATER ACT IS REQUIRED ONLY IF LISTED BELOW:

- NONE LISTED

**INTERNATIONAL CHEMICAL INVENTORY STATUS**

UNLESS OTHERWISE NOTED, THIS PRODUCT IS IN COMPLIANCE WITH THE INVENTORY LISTING OF THE COUNTRIES SHOWN BELOW. FOR INFORMATION ON LISTING FOR COUNTRIES NOT SHOWN, CONTACT DEGUSSA CORPORATION PRODUCT

REGULATORY DEPARTMENT:

- EUROPE (EINECS/ELINCS) LISTED/REGISTERED
- USA (TSCA) LISTED/REGISTERED
- CANADA (DSL) LISTED/REGISTERED
- AUSTRALIA (AICS) LISTED/REGISTERED
- JAPAN (MITI) NOT LISTED/NOT REGISTERED
- KOREA (TCCL) NOT LISTED/NOT REGISTERED
- PHILIPPINES (PICCS) NOT LISTED/NOT REGISTERED
- CHINA LISTED/REGISTERED

===== SECTION XVI- DISCLAIMER =====

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA AVAILABLE TO US AND IS BELIEVED TO BE CORRECT. WOOD KOTE PRODUCTS MAKES NO WARRANTY, EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. WOOD KOTE PRODUCTS ASSUMES NO RESPONSIBILITY FOR INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN.