

**SAFETY DATA SHEET**  
**WOOD KOTE PRODUCTS INC.**  
[www.woodkote.com](http://www.woodkote.com)

**Section 1: Product and Company Identification**

Product Name: Dye Stain Bright Red    Product Code: 462

Trade Name: Dye Stain

**WOOD KOTE PRODUCTS INC.**

8000 NE 14th Place  
Portland, Oregon 97211  
USA

TEL: 503-285-8371

800-843-7666 (Toll Free USA & Canada)

FAX: 503-285-8374

E-MAIL: [info@woodkote.com](mailto:info@woodkote.com)

**EMERGENCY CONTACT**

**INFOTRAC** (Transportation): 800-535-5053

Product Use: This product is intended for professional use and application only.

**Section 2: Hazards Identification**

**GHS Ratings:**

Flammable liquid	2	Flash point < 23°C and initial boiling point > 35°C (95°F)
Eye corrosive	2A	Eye irritant: subcategory 2A, reversible in 21 days.

**GHS Hazards**

H225	Highly flammable liquid and vapour.
H303	May be harmful if swallowed.
H313	May be harmful in contact with skin.
H319	Causes serious eye irritation.
H333	May be harmful if inhaled.

**GHS Precautions**

P210	Keep away from heat/sparks/open flames/hot surfaces - No smoking.
P211	Do not spray on an open flame or other ignition source.
P233	Keep container tightly closed.
P234	Keep only in original container.
P235	Keep cool.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/light/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P285	In case of inadequate ventilation wear respiratory protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing

P337+P313 If eye irritation persists, get medical advice/attention  
P370+P378 In case of fire: Use water fog, "alcohol" foam, dry chemical, or CO2.  
P405 Store locked up.  
P403+P235 Store in a well ventilated place. Keep cool  
P501WK If spilled, contain spilled material and dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Avoid release to the environment.

**Signal Word: Danger**



**HIGHLY FLAMMABLE LIQUID AND VAPOR.  
VAPORS MAY CAUSE FLASH FIRE.**

### Section 3: Composition / Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Acetone	67-64-1	80.00% - 90.00%
Water	7732-18-5	10.00% - 20.00%

### Section 4: First Aid Measures

**IF INHALED:** If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician.

**IF IN EYES:** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention immediately.

**IF ON SKIN:** Remove contaminated clothing/shoes. Flush skin with water for at least 15 minutes. Follow by washing with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned.

**IF SWALLOWED:** DO NOT INDUCE VOMITING. Do not attempt to give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention.

**Note to Physician:** Provide general supportive measures and treat symptomatically.

### Section 5: Fire Fighting Measures

Flash Point: -18 C (0 F)

LEL: 3.00

UEL: 13.00

**GENERAL HAZARD:** Flammable Liquid and Vapor. Contact with strong oxidizers may cause fire.

**EXTINGUISHING MEDIA:** Use water fog, foam, dry chemical, or CO2. Water may be ineffective because it will not cool acetone below its flashpoint.

**EXPLOSION HAZARDS:** When heated above the flash point, this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mists or sprays may be flammable at temperatures below the flashpoint.

**HAZARDOUS COMBUSTION PRODUCTS:** Carbon monoxide and unidentified organic compounds may be formed during combustion.

**FIRE FIGHTING PROCEDURES: DANGER!** Highly flammable liquid and vapor. Vapors are heavier than air. Vapors may travel across the ground and reach remote ignition sources causing a flashback fire danger. Clear fire area of unprotected personnel. Wear positive pressure self-contained breathing apparatus (SCBA). Move containers from fire area if you can do it without risk. Use water spray to cool containers exposed to fire.

**FIRE EQUIPMENT:** Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure, NOISH approved, self-contained breathing apparatus.

## Section 6: Accidental Release Measures

**PERSONAL PRECAUTIONS:** Wear appropriate protective equipment including respiratory protection as conditions warrant. Do not touch or walk through spilled material. Do not touch damaged containers unless wearing appropriate protective clothing.

**EMERGENCY PROCEDURES:** As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Ventilate closed spaces before entering. Approach the spill from upwind and pick up absorbed materials and place it in a suitable container.

**CONTAINMENT/CLEAN-UP MEASURES:** Stop leak if you can do it without risk. All equipment used when handling the product must be grounded. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean non-sparking tools to collect absorbed material. A vapor suppressing foam may be used to reduce vapors.

**LARGE SPILLS:** Dike far ahead of liquid spill for later disposal. Keep material out of storm sewers and ditches which lead to waterways.

## Section 7: Handling and Storage

**HANDLING:** Do not taste or swallow. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

**STORAGE:** Keep away from heat, sparks, and flame. Keep away from sources of ignition. Store in a cool, dry, well-ventilated area away from incompatible substances. Store in flammables area. Keep in original container tightly closed when not in use.

**COMMENTS:** Read label before use. KEEP OUT OF REACH OF CHILDREN! Empty containers, retain product residue (liquid and/or vapor). Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition; they may explode and cause injury or death.

## Section 8: Exposure Control and Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Acetone 67-64-1	TWA 1000 ppm - 2400 mg/m <sup>3</sup>	TWA 500 ppm STEL 750 PPM	NIOSH: TWA 250 ppm 590 mg/m <sup>3</sup>
Water 7732-18-5	NDA	NDA	NDA

**ENGINEERING CONTROLS:** Provide explosion-proof general local exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

**VENTILATION:** General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below TLV. Ventilation equipment must be explosion proof.

### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Wear safety goggles. Maintain eye wash fountain and quick drench facilities in work areas.

**SKIN:** Wear protective gloves. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

**RESPIRATORY:** In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134. Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or symptoms are experienced.

**WORK HYGIENIC PRACTICES:** Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Safety shower and eye wash should be available close to work areas.

**OTHER USE PRECAUTIONS:** May be harmful if swallowed. May irritate body tissues. Use with adequate ventilation. Avoid breathing vapor. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling.

**COMMENTS:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

**CONTAMINATED GEAR:** Take off contaminated clothing and wash it before reuse. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables, use detergent and hot water. Keep and wash PPE separately from other laundry.

## Section 9: Physical and Chemical Properties

<b>Appearance:</b> Liquid / Colored <b>Viscosity:</b> N/A <b>PH</b> N/A <b>Vapor Pressure:</b> 24.7 kPa at 20 deg C/68 deg F (ASTM D-4052) <b>Melting point:</b> -94°C (-137.2°F) <b>Boiling range:</b> 56°C (133°F) <b>Flammable Limits:</b> 2.6 %Vol to 12.8 %Vol <b>Specific Gravity (SG)</b> 0.810 <b>VOC g/L (Material)</b> 0.0	<b>Odor:</b> Pungent Odor. <b>Solubility in Water:</b> Complete. <b>Autoignition temperature:</b> 465°C (869°F) <b>Vapor Density:</b> ~ 2 20 deg C/68 deg F (air = 1) <b>Freezing point:</b> N/A <b>Flash point:</b> ~ -26°C (-15°F) method:IP 170 <b>Evaporation rate:</b> 5.6 (ASTM D3539, nBuAc=1) <b>VOC g/L (Coating)</b> 0.0
--	---

## Section 10: Stability and Reactivity

### Stability:

Under normal conditions:

STABLE

### Incompatibilities:

Strong oxidizers.

Avoid heat, sparks, open flames and other ignition sources.

### Hazardous decomposition:

Carbon monoxide and unidentified organic compounds may be formed during combustion. There should be no decomposition if stored and applied as directed.

Hazardous polymerization will not occur.

## Section 11: Toxicological Information

### Mixture Toxicity

Oral Toxicity LD50: 3,376mg/kg

Inhalation Toxicity LC50: 50mg/L

### Component Toxicity

67-64-1

Acetone

Inhalation LC50: 44 g/m3 (Mouse)

### PRIMARY ROUTES OF ENTRY

Inhalation

Skin Contact

### Effects of Overexposure

Inhalation

Inhalation of high concentrations can produce central nervous system effects such as nausea, headache, dizziness, unconsciousness and coma. Causes respiratory tract irritation. May cause speech abnormalities

## Section 12: Ecological Information

**ENVIRONMENTAL SUMMARY:** Avoid uncontrolled releases of this material. Where spills are possible, comprehensive spill response plan should be developed and implemented. Do not contaminate water when cleaning equipment or disposing of equipment washwaters or rinsate.

### Component Ecotoxicity

Acetone

Environmental Data: Readily biodegradable.

Ecotoxicological Information: Keep out of waterways.

## Section 13: Disposal Considerations

**DISPOSAL:** If spilled, contain spilled material and dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Avoid release to the environment.

## Section 14: Transport Information

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	Acetone	1090	III	2
IATA	Acetone	1090	III	2
IMDG/IMO	Acetone	1090	III	2

## Section 15: Regulatory Information

### SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

**311/312 HAZARD CATEGORIES:** This product should be reported as an immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.

**FIRE:** Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

**313 REPORTABLE INGREDIENTS:** To the best of our knowledge, this product is not listed as a toxic chemical under Section 313 of SARA Title III.

**302/304 EMERGENCY PLANNING. EMERGENCY PLAN:** To the best of our knowledge, this product is not listed as an extremely hazardous substance.

**CALIFORNIA PROPOSITION 65:** To the best of our knowledge this material does not contain any chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

**ACGIH** (American Conference of Governmental Industrial Hygienists)

**TWA** (Time-Weighted Average)

**OSHA** (Occupational Safety and Health Administration)

**NIOSH** (National Institute for Occupational Safety and Health)

## Section 16: Other Information

### ABBREVIATIONS USED IN THE SDS:

NDA: No Data Available

### Hazardous Material Information System (HMIS)

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0
PERSONAL PROTECTION	G

#### HMIS & NFPA Hazard Rating

##### Legend

\* = Chronic Health Hazard


0 = INSIGNIFICANT

1 = SLIGHT

2 = MODERATE

3 = HIGH

### National Fire Protection Association (NFPA)



**DISCLAIMER:** The information contained herein is based on data available to us and is believed to be correct. WOOD KOTE PRODUCTS makes no warranty, expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable. WOOD KOTE PRODUCTS assumes no responsibility for injury from the use of the product described herein. The conditions or methods of handling, storage, use, and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with handling, storage, use or disposal of the product.

Date Revised: 10/28/2015