

M A T E R I A L S A F E T Y D A T A S H E E T

703-WOODPERFECT-RED MHGNY

Page: 1

PRODUCT NAME: 703-WOODPERFECT-RED MHGNY
PRODUCT CODE: 703-PWS

HMIS CODES: H F R P
2 2 0 G

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: WOOD KOTE PRODUCTS INC.
ADDRESS : 8000 NE 14TH PLACE
PORTLAND, OR 97211

EMERGENCY PHONE : (800) 535-5053 DATE PRINTED : 07/10/07
INFORMATION PHONE : (503) 285-8371 NAME OF PREPARER : C. JENKINS

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

Table with 5 columns: REPORTABLE COMPONENTS, CAS NUMBER, VAPOR PRESSURE mm Hg @ TEMP, WEIGHT PERCENT. Rows include Calcium Carbonate, Rheological Additive, Hydroous Aluminum Silicate, and Linseed Fatty Acids Triglycerides.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: N/A SPECIFIC GRAVITY (H2O=1): 1.65
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER
COATING V.O.C.: 158 g/l MATERIAL V.O.C.: 158 g/l
SOLUBILITY IN WATER: NEGLIGABLE
APPEARANCE AND ODOR: THICK REDDISH BROWN PASTE, MILD MINERAL SPIRITS ODOR.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 105 F METHOD USED: TCC
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: .2 OZ/FT UPPER: N/A

EXTINGUISHING MEDIA: ALCOHOL FOAM, CO2, DRY CHEMICAL.

SPECIAL FIREFIGHTING PROCEDURES

DO NOT ENTER ANY ENCLOSED OR CONFINED FIRE SPACE WITHOUT PROPER PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS.

UNUSUAL FIRE AND EXPLOSION HAZARDS

HANDLE AS COMBUSTABLE LIQUID. VAPORS FORM AN EXPLOSIVE MIXTURE IN AIR BETWEEN THE UPPER AND LOWER EXPLOSIVE LIMITS WHICH CAN BE IGNITED BY MANY SOURCES SUCH AS PILOT LIGHTS, OPEN FLAMES, ELECTRICAL MOTORS AND SWITCHES.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE - AVOID EXPOSURE TO EXCESSIVE HEAT.

CONDITIONS TO AVOID

EXCESSIVE HEAT, POOR VENTILATION AND IGNITION SOURCES.

INCOMPATIBILITY (MATERIALS TO AVOID)

AVOID STRONG OXIDIZERS, STRONG ACIDS, AND STRONG BASES.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

NORMAL COMBUSTION FORMS CARBON MONOXIDE, CARBON DIOXIDE, AND OTHER ORGANIC COMPOUNDS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

OVEREXPOSURE TO VAPORS OR FUMES MAY CAUSE DIZZINESS, LOSS OF APPETITE, WEAKNESS, AND LOSS OF COORDINATION.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

EYE CONTACT: MAY CAUSE IRRITATION, TEARING, BLURRED VISION. CAN CAUSE CHEMICAL BURN - DAMAGE IRREVERSIBLE.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

REPEATED OR PROLONGED SKIN CONTACT MAY DRY AND DEFAT SKIN CAUSING CRACKS, IRRITATION, AND DERMITITIS.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

CAN CAUSE GASTROINTESTINAL IRRITATION, VOMITING, NAUSEA, AND DIARRHEA.

HEALTH HAZARDS (ACUTE AND CHRONIC)

HEADACHE, DIZZINESS, LOSS OF APPETITE, WEAKNESS, AND LOSS OF COORDINATION. AFFECTED PERSONS USUALLY EXPERIENCE COMPLETE RECOVERY WHEN REMOVED FROM EXPOSURE AREA TO FRESH AIR. SPECIAL NOTICE: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL. MAY CAUSE LIVER AND KIDNEY DAMAGE.

CARCINOGENICITY: NTP CARCINOGEN: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

PRE-EXISTING EYE, SKIN AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION- MOVE PERSON TO FRESH AIR. IF BREATHING STOPS, APPLY ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION. EYE CONTACT- FLUSH WITH LARGE QUANTITIES OF WATER FOR AT LEAST 15 MINUTES. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. SKIN CONTACT- WASH WITH SOAP AND WATER. INGESTION- DO NOT INDUCE VOMITING, CONTACT A PHYSICIAN OR HOSPITAL EMERGENCY ROOM IMMEDIATELY FOR INSTRUCTIONS.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

EXTINGUISH ALL SOURCES OF IGNITION IN VICINITY OF SPILL OR RELEASED VAPORS.
CLEAN UP AS SOON AS POSSIBLE. PLACE INTO AIRTIGHT CONTAINER.

WASTE DISPOSAL METHOD

DISPOSE OF ANY UNWANTED MATERIAL IN ACCORDANCE WITH ALL LOCAL, STATE, AND
FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

DO NOT USE OR STORE NEAR HEAT, SPARKS, FLAME OR HOT SURFACES. KEEP CONTAINER
CLOSED WHEN NOT IN USE. CAUTION: COMBUSTIBLE. USE WITH ADEQUATE VENTILATION.
KEEP OUT OF REACH OF CHILDREN.

OTHER PRECAUTIONS

SMOKING IN AREAS WHERE THIS MATERIAL IS USED SHOULD BE STRICTLY PROHIBITED.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

IF A MEDIUM OR STRONG ODOR IS NOTICED OR YOU EXPERIENCE EVEN SLIGHT DIZZINESS OR
NAUSEA-STOP-VENTILATION IS INADEQUATE. USE A NIOSH APPROVED CHEMICAL CARTRIDGE
RESPIRATOR FOR ORGANIC VAPORS.

VENTILATION

AREA SHOULD BE WELL VENTILATED. OPEN DOORS AND WINDOWS TO PROVIDE FRESH AIR
ENTRY AND TO PREVENT VAPOR BUILD-UP. EXHAUST EQUIPMENT MUST BE EXPLOSION PROOF.

PROTECTIVE GLOVES

SKIN CONTACT CAN BE AVOIDED BY WEARING RUBBER GLOVES.

EYE PROTECTION

EYE CONTACT CAN BE AVOIDED BY WEARING SAFETY GLASSES OR GOGGLES.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

WEAR CLOTHING SUITABLE TO PROTECT SKIN CONTACT. EMERGENCY EYEWASH STATION
SHOULD BE AVAILABLE IN THE GENERAL WORK AREA.

WORK/HYGIENIC PRACTICES

WASH HANDS BEFORE EATING, DRINKING, SMOKING, OR USING TOILET FACILITIES.

===== SECTION IX - DISCLAIMER =====

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA AVAILABLE TO US AND IS
BELIEVED TO BE CORRECT. WOOD KOTE PRODUCTS MAKES NO WARRANTY, EXPRESSED OR
IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM
THE USE THEREOF. WOOD KOTE PRODUCTS ASSUMES NO RESPONSIBILITY FOR INJURY FROM
THE USE OF THE PRODUCT DESCRIBED HEREIN.