

**SAFETY DATA SHEET**  
**WOOD KOTE PRODUCTS INC.**  
[www.woodkote.com](http://www.woodkote.com)

## **Section 1: Product and Company Identification**

Product Name: Glaze Kote 250 - Burnt Umber    Product Code: 513

**WOOD KOTE PRODUCTS INC.**

8000 NE 14th Place  
Portland, Oregon 97211  
USA

TEL: 503-285-8371  
800-843-7666 (Toll Free USA & Canada)  
FAX: 503-285-8374  
E-MAIL: [info@woodkote.com](mailto:info@woodkote.com)

**EMERGENCY CONTACT**

INFOTRAC (Transportation): 800-535-5053

Product Use: Grain Enhacing Glaze. This product is intended for professional use and application only.

## **Section 2: Hazards Identification**

**GHS Ratings:**

Flammable liquid	3	Flash point >= 23°C and <= 60°C (140°F)
Skin corrosive	1A	Destruction of dermal tissue: exposure < 3 min. Observation < 1 hour, visible necrosis in at least one animal.
Eye corrosive	1	Serious eye damage: irreversible damage 21 days after exposure. Draize score: Corneal opacity >= 3, Iritis > 1.5.
Carcinogen	2	Limited evidence of human or animal carcinogenicity.

**GHS Hazards**

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H351	Suspected of causing cancer.

**GHS Precautions**

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/light/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe mist/vapours/spray.
P264	Wash skin thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P285	In case of inadequate ventilation wear respiratory protection.
P310	Immediately call a POISON CENTER or doctor/physician.
P363	Wash contaminated clothing before reuse.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing

P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P308+P313	IF exposed or concerned: Get medical advice/attention
P332+P313	If skin irritation occurs: Get medical advice/attention
P337+P313	If eye irritation persists, get medical advice/attention
P370+P378	In case of fire: Use water fog, "alcohol" foam, dry chemical, or CO <sub>2</sub> .
P405	Store locked up.
P403+P235	Store in a well ventilated place. Keep cool
P501WK	If spilled, contain spilled material and dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Avoid release to the environment.

#### Signal Word: Danger



FLAMMABLE LIQUID AND VAPOR

#### Section 3: Composition / Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
4-Chlorobenzotrifluoride	98-56-6	20.00% - 30.00%
Trade Secret	Trade Secret	10.00% - 20.00%
Hydrous Aluminum Silicate	1332-58-7	10.00% - 20.00%
Solvent Naphtha (petroleum), Medium Aliphatic	64742-88-7	10.00% - 20.00%
Alkyd Resin	Proprietary 4	5.00% - 10.00%
Talc	14807-96-6	1.00% - 5.00%
Manganese (IV) Oxide	1313-13-9	1.00% - 5.00%
Iron (III) Oxide	1309-37-1	1.00% - 5.00%
Mineral Spirits	8052-41-3	1.00% - 5.00%
Xylene (o-,m-,p- isomers)	1330-20-7	1.00% - 5.00%
Silicon Dioxide	14808-60-7	0.10% - 1.00%
Carbon Black	1333-86-4	0.10% - 1.00%

#### Section 4: First Aid Measures

**IF INHALED:** If breathing is difficult, remove source of exposure or move victim to fresh air and keep at rest in a position comfortable for breathing. If victim is not breathing, call 911 and administer CPR as directed.

**IF IN EYES:** Rinse eyes cautiously with lukewarm, gently flowing water for 15 minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing. Take care not to rinse contaminated water into the unaffected eye or onto the face. Get immediate medical attention.

**IF ON SKIN:** Rinse/wash with lukewarm, gently flowing water (and mild soap) for 15 minutes or until product is removed. If skin irritation occurs or you feel unwell: Get medical advice/attention.

**IF SWALLOWED:** DO NOT INDUCE VOMITING. Do not attempt to give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Immediately call a POISON CENTER/doctor.

**Note to Physician:** Provide general supportive measures and treat symptomatically.

## Section 5: Fire Fighting Measures

Flash Point: 40 C (104 F)

LEL: 1.00

UEL: 11.00

**EXTINGUISHING MEDIA:** Use water fog, foam, dry chemical, or CO<sub>2</sub>.

**EXPLOSION HAZARDS:** When heated above the flash point, this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mists or sprays may be flammable at temperatures below the flashpoint.

**FIRE FIGHTING PROCEDURES: WARNING!** Flammable liquid and vapor. Vapors are heavier than air. Vapors may travel across the ground and reach remote ignition sources causing a flashback fire danger. Clear fire area of unprotected personnel. Wear positive pressure self-contained breathing apparatus (SCBA). Move containers from fire area if you can do it without risk. Use water spray to cool containers exposed to fire.

**FIRE EQUIPMENT:** Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure, NIOSH approved, self-contained breathing apparatus.

## Section 6: Accidental Release Measures

**PERSONAL PRECAUTIONS:** Wear appropriate protective equipment including respiratory protection as conditions warrant. Do not touch or walk through spilled material. Do not touch damaged containers unless wearing appropriate protective clothing.

**EMERGENCY PROCEDURES:** As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Ventilate closed spaces before entering.

**CONTAINMENT/CLEAN-UP MEASURES:** Stop leak if you can do it without risk. All equipment used when handling the product must be grounded. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean non-sparking tools to collect absorbed material. A vapor suppressing foam may be used to reduce vapors.

**LARGE SPILLS:** Dike far ahead of liquid spill for later disposal. Keep material out of storm sewers and ditches which lead to waterways.

## Section 7: Handling and Storage

**HANDLING:** Do not taste or swallow. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

**STORAGE:** Keep in original container tightly closed when not in use and stored away from direct light at temperatures between 32-110°F (0-43°C).

**COMMENTS:** Read label before use. KEEP OUT OF REACH OF CHILDREN! Empty containers, retain product residue (liquid and/or vapor). Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition; they may explode and cause injury or death.

## Section 8: Exposure Control and Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
4-Chlorobenzotrifluoride 98-56-6	TWA 2.5 mg/m <sup>3</sup>	TWA 2.5 mg/m <sup>3</sup>	NDA
Trade Secret Trade Secret	Not Established	Not Established	Not Established
Hydrous Aluminum Silicate 1332-58-7	TWA 10 mg/m <sup>3</sup>	TWA 2 mg/m <sup>3</sup>	NIOSH: TWA 5 mg/m <sup>3</sup>
Solvent Naphtha (petroleum) , Medium Aliphatic 64742-88-7	PEL 500 ppm 2,900 mg/m <sup>3</sup> TWA 100 ppm 525 mg/m <sup>3</sup>	TWA 100 ppm	NDA
Alkyd Resin Proprietary 4	NDA	NDA	NDA

Talc 14807-96-6	TWA 20 Million particles per cubic foot	TWA 2,000 mg/m <sup>3</sup>	NIOSH: TWA 2 mg/m <sup>3</sup>
Manganese (IV) Oxide 1313-13-9	CEILING: 5 mg/m <sup>3</sup>	TWA 0.2 mg/m <sup>3</sup>	NIOSH: TWA 1 mg/m <sup>3</sup> ST 2 mg/m <sup>3</sup>
Iron (III) Oxide 1309-37-1	TWA 15 mg/m <sup>3</sup>	TWA 5 mg/m <sup>3</sup>	TWA 5 mg/m <sup>3</sup>
Mineral Spirits 8052-41-3	TWA 500 ppm 2900 mg/m <sup>3</sup>	TWA 100 ppm	NIOSH IDLH:20000 mg/m <sup>3</sup> TWA: 350 MG/M <sup>3</sup>
Xylene (o-,m-,p- isomers) 1330-20-7	TWA 100 ppm 435 mg/m <sup>3</sup>	STEL: 150 ppm TWA: 100 ppm	TWA 100 ppm 435 mg/m <sup>3</sup>
Silicon Dioxide 14808-60-7	TWA 30 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	TWA 0.025 mg/m <sup>3</sup>	NIOSH: TWA 0.05 mg/m <sup>3</sup>
Carbon Black 1333-86-4	TWA 3.5 mg/m <sup>3</sup>	TWA 3.5 mg/m <sup>3</sup>	NIOSH: TWA 3.5 mg/m <sup>3</sup>

**ENGINEERING CONTROLS:** Provide general local exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

**VENTILATION:** General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below TLV. Ventilation equipment must be explosion proof.

#### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Wear safety goggles. Maintain eye wash fountain and quick drench facilities in work areas.

**SKIN:** Wear protective gloves. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

**RESPIRATORY:** In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134. Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or symptoms are experienced.

**WORK HYGIENIC PRACTICES:** Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Safety shower and eye wash should be available close to work areas.

**OTHER USE PRECAUTIONS:** May be harmful if swallowed. May irritate body tissues. Use with adequate ventilation. Avoid breathing vapor. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling.

**COMMENTS:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

**CONTAMINATED GEAR:** Take off contaminated clothing and wash it before reuse. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables, use detergent and hot water. Keep and wash PPE separately from other laundry.

#### Section 9: Physical and Chemical Properties

<b>Appearance:</b> Viscous Liquid / Colored <b>Autoignition temperature:</b> 230°C <b>Vapor Density:</b> 4.8 <b>Melting point:</b> N/A <b>Solubility in Water:</b> 29 ppm @ 23°C <b>Flash point:</b> 40 C, 104 F <b>Specific Gravity (SG)</b> 1.365 <b>VOC g/L (Coating)</b> 147	<b>Odor:</b> Stoddard and Slightly Pungent <b>Vapor Pressure:</b> 295.4 Pa at 20 C <b>PH</b> N/A <b>Freezing point:</b> N/A <b>Boiling point:</b> 137°C <b>LEL/UEL</b> 1% - 11% <b>VOC g/L (Material)</b> 248
-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

## Section 10: Stability and Reactivity

### Stability:

Under normal conditions:

STABLE

### Incompatibilities:

No decomposition if used and stored according to specifications.

Strong oxidizers.

**Chemical stability:** Stable under recommended storage conditions.

Avoid heat, sparks, open flames and other ignition sources.

### Hazardous decomposition:

Carbon monoxide and carbon dioxide.

Oxygen, hydrogen gas, water, heat, steam.

Hazardous polymerization will not occur.

## Section 11: Toxicological Information

### Mixture Toxicity

Inhalation Toxicity LC50: 85mg/L

### Component Toxicity

98-56-6            4-Chlorobenzotrifluoride  
Oral LD50: 7 g/kg (Rat) Dermal LD50: 3 g/kg (Rabbit)

64742-88-7       Solvent Naphtha (petroleum), Medium Aliphatic  
Dermal LD50: 3,000 mg/kg (Rabbit) Inhalation LC50: 14 mg/L (Rat)

1333-86-4       Carbon Black  
Dermal LD50: 3,000 mg/kg (Rabbit)

### PRIMARY ROUTES OF ENTRY

Inhalation      Skin Contact      Eye Contact      Ingestion

Target Organs: Eyes, skin.

## Section 12: Ecological Information

**ENVIRONMENTAL SUMMARY:** Avoid uncontrolled releases of this material. Where spills are possible, comprehensive spill response plan should be developed and implemented. Do not contaminate water when cleaning equipment or disposing of equipment washwaters or rinsate.

### Component Ecotoxicity

Solvent Naphtha (petroleum),      Very toxic for fish.  
Medium Aliphatic

## Section 13: Disposal Considerations

**DISPOSAL:** If spilled, contain spilled material and dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Avoid release to the environment.

## Section 14: Transport Information

Agency	Proper Shipping Name	UN Number	Packing Group	Hazard Class
DOT	Paint	1263	III	3
IATA	Paint	1263	III	3
IMDG/IMO	Paint	1263	III	3

## Section 15: Regulatory Information

ACGIH (American Conference of Governmental Industrial Hygienists)  
TWA (Time-Weighted Average)  
OSHA (Occupational Safety and Health Administration)  
NIOSH (National Institute for Occupational Safety and Health)

## Section 16: Other Information

### ABBREVIATIONS USED IN THE SDS:

NDA: No Data Available

### Hazardous Material Information System (HMIS)


HEALTH	2
FLAMMABILITY	2
PHYSICAL HAZARD	0
PERSONAL PROTECTION	G

#### HMIS & NFPA Hazard Rating

##### Legend

- \* = Chronic Health Hazard
- 0 = INSIGNIFICANT
- 1 = SLIGHT
- 2 = MODERATE
- 3 = HIGH

### National Fire Protection Association (NFPA)



**DISCLAIMER:** The information contained herein is based on data available to us and is believed to be correct. WOOD KOTE PRODUCTS makes no warranty, expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable. WOOD KOTE PRODUCTS assumes no responsibility for injury from the use of the product described herein. The conditions or methods of handling, storage, use, and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with handling, storage, use or disposal of the product.

Date Revised: 10/19/2015