

**SAFETY DATA SHEET**  
**WOOD KOTE PRODUCTS INC.**  
www.woodkote.com

**Section 1: Product and Company Identification**

Product Name: Jel'd Stain H2O - Cherry Product Code: 2704

**WOOD KOTE PRODUCTS INC.**  
8000 NE 14th Place  
Portland, Oregon 97211  
USA

TEL: 503-285-8371  
800-843-7666 (Toll Free USA & Canada)  
FAX: 503-285-8374  
E-MAIL: info@woodkote.com

**EMERGENCY CONTACT**  
**INFOTRAC** (Transportation): 800-535-5053

Product Use: Water-Based Gelled Stain. This product is intended for professional use and application only.

**Section 2: Hazards Identification**

**GHS Hazards**

H317 May cause an allergic skin reaction.  
H333 May be harmful if inhaled.

**GHS Precautions**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P260 Do not breathe mist/vapours/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P281 Use personal protective equipment as required.  
P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P302+P350 IF ON SKIN: Gently wash with soap and water.  
P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P370+P378 In case of fire: Use water fog, "alcohol" foam, dry chemical, or CO2.  
P405 Store locked up.  
P501WK If spilled, contain spilled material and dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Avoid release to the environment.

**Signal Word: Warning**



### Section 3: Composition / Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Water	7732-18-5	40.00% - 50.00%
Alkyd Polymer	Proprietary 3	10.00% - 20.00%
Propylene Glycol	57-55-6	5.00% - 10.00%
Ammonium salt of modified acrylic copolymers	9003-03-6	5.00% - 10.00%
Polypropylene Glycol	25322-69-4	5.00% - 10.00%
Yellow Iron Oxide	51274-00-1	1.00% - 5.00%
Raw Umbers, Burnt Umbers	12713-03-0	1.00% - 5.00%
Iron Oxide	1332-37-2	1.00% - 5.00%
Dipropylene Glycol Methyl Ether	34590-94-8	1.00% - 5.00%
Trade Secret	Trade Secret	1.00% - 5.00%

### Section 4: First Aid Measures

**IF INHALED:** If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

**IF ON SKIN:** Gently wash with plenty of soap and water.

**IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting.

**Note to Physician:** Provide general supportive measures and treat symptomatically.

### Section 5: Fire Fighting Measures

Flash Point: 100 C (212 F)

LEL: 3.00

UEL: 13.00

**EXTINGUISHING MEDIA:** Use water fog, foam, dry chemical, or CO<sub>2</sub>.

**EXPLOSION HAZARD:** Material will not support combustion unless the water has evaporated. Unopened containers exposed to extreme heat may build that pressure and rupture. Cool unopened containers with water.

**HAZARDOUS COMBUSTION PRODUCTS:** Carbon monoxide and unidentified organic compounds may be formed during combustion.

**FIRE FIGHTING PROCEDURES:** Not combustible as supplied. However, it is advisable to wear self-contained breathing apparatus when fighting fires involving this material to avoid inhalation of decomposition by-products.

### Section 6: Accidental Release Measures

**PERSONAL PRECAUTIONS:** Wear appropriate protective equipment including respiratory protection as conditions warrant. Do not touch or walk through spilled material. Do not touch damaged containers unless wearing appropriate protective clothing.

**SMALL SPILLS:** Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use.

**LARGE SPILLS:** Dike far ahead of liquid spill for later disposal. Keep material out of storm sewers and ditches which lead to waterways.

### Section 7: Handling and Storage

**HANDLING:** PREVENT/ KEEP FROM FREEZING. Do not taste or swallow. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

**STORAGE:** PREVENT/ KEEP FROM FREEZING. Keep in original container tightly closed when not in use and stored away from direct light at temperatures between 40-110°F (4.5-43°C).

**COMMENTS:** Read label before use. KEEP OUT OF REACH OF CHILDREN! Empty containers, retain product residue (liquid and/or vapor).

## Section 8: Exposure Control and Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Water 7732-18-5	NDA	NDA	NDA
Alkyd Polymer Proprietary 3	NDA	NDA	NDA
Propylene Glycol 57-55-6	NDA	NDA	WEEL: TWA 10 mg/m3
Ammonium salt of modified acrylic copolymers 9003-03-6	NDA	NDA	NDA
Polypropylene Glycol 25322-69-4	NDA	NDA	WEEL: TWA 10 mg/m3
Yellow Iron Oxide 51274-00-1	NDA	NDA	NDA
Raw Umbers, Burnt Umbers 12713-03-0	TWA 10 mg/m3	TWA 5 mg/m3	NDA
Iron Oxide 1332-37-2	TWA 10 mg/M3	TWA 5 mg/m3	NDA
Dipropylene Glycol Methyl Ether 34590-94-8	TWA 100 ppm 600 mg/m3	TWA 100 ppm STEL 150 ppm	NIOSH: TWA 100 ppm 600 mg/m3
Trade Secret	NDA	NDA	NDA

**ENGINEERING CONTROLS:** Provide general local exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

**VENTILATION:** Good general ventilation should be used. Ventilation rates should be matched to conditions.

### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Wear safety goggles. Maintain eye wash fountain and quick drench facilities in work areas.

**SKIN:** Wear protective gloves. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

**RESPIRATORY:** In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134. Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or symptoms are experienced.

**WORK HYGIENIC PRACTICES:** Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Safety shower and eye wash should be available close to work areas.

**OTHER USE PRECAUTIONS:** May be harmful if swallowed. May irritate body tissues. Use with adequate ventilation. Avoid breathing vapor. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling.

**COMMENTS:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

**CONTAMINATED GEAR:** Take off contaminated clothing and wash it before reuse. Follow manufacturer's instructions for cleaning. If no such instructions for washables, use detergent and hot water.

## Section 9: Physical and Chemical Properties

<p><b>Appearance:</b> Gelatinous</p> <p><b>Viscosity:</b> N/A</p> <p><b>PH</b> Essentially neutral.</p> <p><b>Decomposition temperature:</b> N/A</p> <p><b>Melting point:</b> N/A</p> <p><b>Boiling range:</b> 100 - 187°C</p> <p><b>Evaporation rate:</b> Slower than ether.</p> <p><b>VOC g/L (Material)</b> 117.9</p>	<p><b>Odor:</b> Pleasant</p> <p><b>Solubility in Water:</b> Complete</p> <p><b>Autoignition temperature:</b> 305°C</p> <p><b>Vapor Density:</b> Heavier Than Air</p> <p><b>Freezing point:</b> N/A</p> <p><b>Flash point:</b> N/A</p> <p><b>Specific Gravity (SG)</b> 1.109</p> <p><b>VOC g/L (Coating)</b> 247.3</p>
--	---

## Section 10: Stability and Reactivity

**Stability:**

Under normal conditions:

STABLE

**Incompatibilities:**

NDA

**Hazardous decomposition:**

Hazardous polymerization will not occur.

## Section 11: Toxicological Information

**Component Toxicity**

25322-69-4 Polypropylene Glycol  
Oral LD50: 2,000 mg/kg (Rat) Dermal LD50: 3,000 mg/kg (Rabbit)

**PRIMARY ROUTES OF ENTRY**

Inhalation

**Target Organs:** Lungs

## Section 12: Ecological Information

**ENVIRONMENTAL SUMMARY:** Avoid uncontrolled releases of this material. Where spills are possible, comprehensive spill response plan should be developed and implemented. Do not contaminate water when cleaning equipment or disposing of equipment washwaters or rinsate.

**Component Ecotoxicity**

Propylene Glycol	Toxicity to fish: Mortality NOEC-Pimephales promelas (fathead minnow)-52,930 mg/l-96 h Toxicity to daphnia and other aquatic invertebrates: Mortality NOEC-Daphnia (water flea)-13,020 mg/l-48 h EC50-Daphnia magna (Water flea)-> 10,000 mg/l-48 h
Polypropylene Glycol	Toxicity to fish: Static test LC50-Danio rerio (zebra fish)-> 100 mg/l-96 h(OECD Test Guideline 203)

## Section 13: Disposal Considerations

**DISPOSAL:** If spilled, contain spilled material and dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Avoid release to the environment.

**Section 14: Transport Information**

Agency      Proper Shipping Name      UN Number      Packing Group      Hazard Class  
NDA

**Section 15: Regulatory Information**

ACGIH (American Conference of Governmental Industrial Hygienists)

TWA (Time-Weighted Average)

OSHA (Occupational Safety and Health Administration)

NIOSH (National Institute for Occupational Safety and Health)

**OSHA: Occupational Safety and Health Administration.**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):**

This product does not contain chemicals that are listed by the State of California as carcinogenic or a reproductive toxin.

**SARA TITLE III (Superfund Amendment and Reauthorization Act)**

**SARA 302 Components:**

No chemicals in this product are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 311/312 Hazards:**

34590-94-8 Dipropylene Glycol Methyl Ether 1 to 5 % Fire Hazard, Chronic Health Hazard.

**SARA 313 Components:**

No chemicals in this product are subject to the reporting requirements of SARA Title III, Section 313.

**Section 16: Other Information**

**ABBREVIATIONS USED IN THE SDS:**

NDA: No Data Available

**Hazardous Material Information System (HMIS)**

HEALTH	2
FLAMMABILITY	2
PHYSICAL HAZARD	0
PERSONAL PROTECTION	G

HMIS & NFPA Hazard Rating

Legend

\* = Chronic Health Hazard


0 = INSIGNIFICANT

1 = SLIGHT

2 = MODERATE

3 = HIGH

**National Fire Protection Association (NFPA)**



**DISCLAIMER:** The information contained herein is based on data available to us and is believed to be correct. WOOD KOTE PRODUCTS makes no warranty, expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable. WOOD KOTE PRODUCTS assumes no responsibility for injury from the use of the product described herein. The conditions or methods of handling, storage, use, and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with handling, storage, use or disposal of the product.

Date Revised: 2/16/2016