

M A T E R I A L S A F E T Y D A T A S H E E T

WATER BASED JEL'D STAIN ALL COLORS

PRODUCT NAME: JEL'D STAIN H2O ALL COLORS

HMIS CODES: H F R P

PRODUCT CODE: 2706-GSS

1 0 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: WOOD KOTE PRODUCTS INC.

ADDRESS : 8000 NE 14TH PLACE
PORTLAND, OR 97211

EMERGENCY PHONE : (800) 535-5053

DATE PRINTED : 10/01/10

INFORMATION PHONE : (503) 285-8371

NAME OF PREPARER : C. JENKINS

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER mm	VAPOR PRESSURE Hg @ TEMP	WEIGHT PERCENT
ALKYD EMULSION	PROPRIETARY		40 TO 50
EXPOSURE LIMITS NOT ESTABLISHED			
POLYETHYLENE GLYCOL	25322-68-3		10 TO 20
PROPYLENE GLYCOL	57-55-6	0.129 72 F	5 TO 10
TWA AEROSOL: 10mg/m3			
OXIDE PIGMENTS	PROPRIETARY		0 TO 30

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 212 F - 370 F

SPECIFIC GRAVITY (H2O=1): 1.02-1.05

VAPOR DENSITY: HEAVIER THAN AIR

EVAPORATION RATE: SLOWER THAN ETHER

COATING V.O.C.: <250 g/l

MATERIAL V.O.C.: <250 g/l

SOLUBILITY IN WATER: COMPLETE

APPEARANCE AND ODOR: GELL, PLEASANT ODOR.

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: N/A

METHOD USED:

FLAMMABLE LIMITS IN AIR BY VOLUME-

LOWER:

UPPER:

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG/SPRAY.

SPECIAL FIREFIGHTING PROCEDURES

NOT COMBUSTIBLE AS SUPPLIED. HOWEVER, IT IS ADVISABLE TO WEAR SELF CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES INVOLVING THIS MATERIAL TO AVOID INHALATION OF DECOMPOSITION BY-PRODUCTS.

UNUSUAL FIRE AND EXPLOSION HAZARDS

MATERIAL WILL NOT SUPPORT COMBUSTION UNLESS THE WATER HAS EVAPORATED. UNOPENED CONTAINERS EXPOSED TO EXTREME HEAT MAY BUILD UP PRESSURE AND RUPTURE. COOL UNOPENED CONTAINERS WITH WATER.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE - AVOID EXPOSURE TO EXCESSIVE HEAT.

CONDITIONS TO AVOID

AVOID EXTREME TEMPERATURES. KEEP FROM FREEZING AND EXPOSURE TO HEAT.

INCOMPATIBILITY (MATERIALS TO AVOID)
AVOID STRONG OXIDIZERS, STRONG ACIDS, AND STRONG BASES.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS
CARBON MONOXIDE, CARBON DIOXIDE, AND POSSIBLY NITROGEN OXIDES. OTHER ORGANIC
COMPOUNDS MAY ALSO BE FORMED.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
INHALATION OF VAPOR OR MIST MAY CAUSE IRRITATION OF NASAL PASSAGES AND THROAT.
HEADACHE, NAUSEA AND DIZZINESS MAY ALSO OCCUR.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE
PROLONGED OR REPEATED SKIN CONTACT MAY DRY AND DEFAT SKIN, CAUSING CRACKS,
IRRITATION, AND DERMATITIS. EYE CONTACT CAN CAUSE IRRITATION, REDNESS, AND
TEARING.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
NONE KNOWN.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION, VOMITING, NAUSEA, AND
DIARRHEA. INGESTION MAY BE HARMFUL.

HEALTH HAZARDS (ACUTE AND CHRONIC)
NO LONG TERM HEALTH EFFECTS ARE EXPECTED.

CARCINOGENICITY: NTP CARCINOGEN: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE
PRE-EXISTING SKIN CONDITIONS COULD BE AGGRAVATED BY OVEREXPOSURE.

EMERGENCY AND FIRST AID PROCEDURES
EYE CONTACT: CHECK FOR AND REMOVE CONTACT LENSES. FLUSH EYES WITH RUNNING WATER
FOR AT LEAST 15 MINUTES. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION.
SKIN CONTACT: WASH AFFECTED AREA SOAP AND WATER. WASH CONTAMINATED CLOTHING
BEFORE REUSE.
INHALATION: REMOVE AFFECTED INDIVIDUAL TO FRESH AIR. IF BREATHING HAS
STOPPED, APPLY ARTIFICIAL RESPIRATION. GET MEDICAL ATTENTION.
INGESTION: IF SWALLOWED, GET MEDICAL ATTENTION. DO NOT INDUCE VOMITING
UNLESS INSTRUCTED TO DO SO BY MEDICAL PERSONNEL. SEEK IMMEDIATE MEDICAL
ATTENTION.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
CONTAIN SPILLED LIQUID. FOR SMALL SPILLS, ADD DRY MATERIAL TO CONTAIN. REMOVE
BULK OF LIQUID AND ADD DRY MATERIAL TO ABSORB REMAINING LIQUID. CONTAINERIZE
FOR DISPOSAL. FLUSH AREA WITH WATER TO REMOVE RESIDUES.

WASTE DISPOSAL METHOD
DISPOSE OF ANY UNWANTED MATERIAL IN ACCORDANCE WITH ALL LOCAL, STATE, AND
FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
STORE IN WELL VENTILATED AREA TO AVOID BUILD-UP OF VAPOR CONCENTRATIONS. STORE
AT TEMPERATURES BETWEEN 40F AND 90F. KEEP FROM FREEZING.

OTHER PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN.

KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE.

NOTICE: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS OF THIS PRODUCT MAY BE HARMFUL.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

AVOID PROLONGED OR REPEATED BREATHING OF VAPORS. IF EXPOSURE MAY OR DOES EXCEED OCCUPATIONAL EXPOSURE LIMITS (SEC II) USE A NIOSH-APPROVED RESPIRATOR TO PREVENT OVEREXPOSURE. IN ACCORDANCE WITH 29 CFR 1910.134 USE EITHER AN AIR PURIFYING RESPIRATOR FOR ORGANIC VAPORS OR AN AIR SUPPLIED SELF CONTAINED BREATHING APPARATUS.

VENTILATION

LOCAL EXHAUST SHOULD BE SUFFICIENT TO KEEP VAPORS BELOW THE THRESHOLD LIMIT VALUES. OPEN DOORS AND WINDOWS TO PROVIDE FRESH AIR ENTRY AND TO PREVENT VAPOR BUILD-UP.

PROTECTIVE GLOVES

SKIN CONTACT CAN BE AVOIDED BY WEARING RUBBER GLOVES.

EYE PROTECTION

EYE CONTACT CAN BE AVOIDED BY WEARING SAFETY GLASSES OR GOGGLES.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

WEAR CLOTHING THAT WILL PROTECT THE SKIN FROM CONTACT WITH THIS MATERIAL.

WORK/HYGIENIC PRACTICES

WASH HANDS BEFORE EATING, DRINKING, SMOKING, OR USING TOILET FACILITIES. EYE WASH STATION AND SAFETY SHOWER IN THE WORKPLACE ARE RECOMMENDED.

===== SECTION IX - DISCLAIMER =====

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA AVAILABLE TO US AND IS BELIEVED TO BE CORRECT. WOOD KOTE PRODUCTS MAKES NO WARRANTY, EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. WOOD KOTE PRODUCTS ASSUMES NO RESPONSIBILITY FOR INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN.