308-JEL'D STAIN 550-HERITAGE OAK

Page: 1

2 2 0 G

HMIS CODES: H F R P

**PRODUCT NAME:** 308-JEL'D STAIN 550-HERITAGE OAK **PRODUCT CODE:** 308-RGS-GSS-507-1

## 

MANUFACTURER'S NAME:WOOD KOTE PRODUCTS INC.ADDRESS: 8000 NE 14TH PLACE<br/>PORTLAND, OR 97211

 EMERGENCY PHONE
 : (800) 535-5053
 DATE PRINTED
 : 10/01/10

 INFORMATION PHONE
 : (503) 285-8371
 NAME OF PREPARER
 : C. JENKINS

## ======= SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION ========

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
ALKYD RESIN SOLUTION	8052-41-3	1.85 68 F	25 TO 35
TLV MINERAL SPIRITS 100 ppm	00045 05 0		15 - 05
PETROLEUM SOLVENT NAPHTHA OSHA PEL 100 ppm	92045-37-9	5 68 F	15 TO 25
ACGIH TLV 100 ppm			
SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPHAT	IC64742-88-7	.37 100 F	10 TO 15
OSHA PEL/TWA 100 ppm			
ACGIH TLV/TWA 100 ppm			
SYNTHETIC ISOPARIFFINIC HYDROCARBON	64742-46-7	<0.1 68øF	
ACGIH: TLV 5 MG/M3			
CARBON BLACK	1333-86-4	N/A N/A	
ACGIH TLV: 3.5 MG/M3 TWA			
OSHA PEL : 3.5 MG/M3 TWA			

BOILING RANGE: 282-372 FSPECIFIC GRAVITY (H2O=1): 0.94VAPOR DENSITY: HEAVIER THAN AIREVAPORATION RATE: SLOWER THAN ETHERCOATING V.O.C.: 550 g/lMATERIAL V.O.C.: 487 g/lSOLUBILITY IN WATER: NEGLIGABLEAPPEARANCE AND ODOR: THICK GEL, PETROLEUM ODOR

FLASH POINT: 104 F METHOD USED: TCC FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: .007 UPPER: 7.00

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL.

## SPECIAL FIREFIGHTING PROCEDURES

SELF CONTAINED BREATHING APPARATUS AND PROTECTIVE EQUIPMENT SHOULD BE WORN WHEN FIGHTING FIRES INVOLVING THIS MATERIAL TO AVOID INHALATION OF HAZARDOUS DECOMPOSITION BY-PRODUCTS. USE WATER AS A FOG TO COOL UNOPENED CONTAINERS ONLY.

## UNUSUAL FIRE AND EXPLOSION HAZARDS

HANDLE AS A COMBUSTIBLE LIQUID. VAPORS FORM EXPLOSIVE MIXTURE IN AIR BETWEEN THE UPPER AND LOWER EXPLOSIVE LIMITS WHICH CAN BE IGNITED BY MANY SOURCES SUCH AS PILOT LIGHTS, OPEN FLAMES, ELECTRICAL MOTOR AND SWITCHES. UNOPENED CONTAINERS EXPOSED TO EXTREME HEAT MAY RUPTURE EXPLOSIVELY. USE WATER AS A FOG TO COOL UNOPENED CONTAINERS.

308-JEL'D STAIN 550-HERITAGE OAK

2 Page:

**STABILITY:** STABLE - AVOID EXPOSURE TO EXCESSIVE HEAT.

#### CONDITIONS TO AVOID

AVOID EXPOSURE TO HEAT, SPARKS, AND OPEN FLAME.

#### INCOMPATIBILITY (MATERIALS TO AVOID)

AVOID STRONG ACIDS AND OXIDIZING AGENTS.

## HAZARDOUS DECOMPOSITION OR BYPRODUCTS

NORMAL COMBUSTION FORMS CARBON MONOXIDE, CARBON DIOXIDE, AND OTHER ORGANIC COMPOUNDS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

## 

## INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

INHALATION OF HIGH VAPOR CONCENTRATIONS MAY CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION, DIZZINESS, WEAKNESS, LOSS OF APPETITE AND LOSS OF COORDINATION. AFFECTED PERSONS USUALLY EXPERIENCE COMPLETE RECOVERY WHEN REMOVED FROM EXPOSURE AREA.

## SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

PROLONGED OR REPEATED SKIN CONTACT MAY DRY AND DEFAT SKIN, CAUSING CRACKS, IRRITATION, AND DERMATITIS. EYE CONTACT CAN CAUSE IRRITATION, REDNESS, AND TEARING.

# SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

NONE KNOWN.

## INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

CAN CAUSE GASTROINTESTINAL IRRITATION, VOMITING, NAUSEA, AND DIARRHEA. VOMITING THIS MATERIAL MAY LEAD TO ASPIRATION OF PETROLEUM DISTILLATES INTO THE LUNGS, RESULTING IN CHEMICAL PNEUMONITIS, EDEMA, AND EVEN DEATH.

## HEALTH HAZARDS (ACUTE AND CHRONIC)

CHRONIC OVEREXPOSURE MAY RESULT IN IRRITATION TO THE EYES, NOSE, THROAT, AND MUCOUS MEMBRANES. NOTICE: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE DAMAGE. CONTENTS MAY BE HARMFUL OR FATAL. MAY CAUSE LIVER AND KIDNEY DAMAGE. BECAUSE THIS PRODUCT IS A FREE FLOWING LIQUID OR PASTE, DUST INHALATION IS NOT AN EXPECTED ROUTE OF EXPOSURE.

#### CARCINOGENICITY: NTP CARCINOGEN: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO

#### MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

PRE-EXISTING EYE, SKIN AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE. CENTRAL NERVOUS SYSTEM DISORDERS MAY ALSO BE AGGRAVATED.

## 308-JEL'D STAIN 550-HERITAGE OAK

Page: 3

## EMERGENCY AND FIRST AID PROCEDURES

INHALATION-MOVE PERSON TO FRESH AIR. IF BREATHING STOPS, APPLY ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION. EYE CONTACT-FLUSH WITH LARGE QUANTITIES OF WATER FOR AT LEAST 15 MINUTES. SKIN CONTACT-WASH AFFECTED AREA THOROUGHLY WITH SOAP AND WATER. INGESTION-DO NOT INDUCE VOMITING. CONTACT PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. TREAT SYMPTOMATICALLY. NOTE: INGESTION OR SUBSEQUENT VOMITING CAN RESULT IN ASPIRATION OF LIGHT HYDROCARBON LIQUID WHICH CAN CAUSE PNEUMONITIS.

## 

#### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

REMOVE ALL SOURCE OF IGNITION. VENTILATE AREA BY OPENING DOORS AND WINDOWS. CONTAIN AND ABSORB MATERIAL, COVER WITH WATER AND PLACE IN AIRTIGHT METAL CONTAINERS.

## WASTE DISPOSAL METHOD

DISPOSE OF ANY UNWANTED MATERIAL IN ACCORDANCE WITH ALL LOCAL, STATE, AND FEDERAL REGULATIONS.

## PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

TURN OFF ALL IGNITION SOURCES PRIOR TO USE AND UNTIL ALL VAPORS ARE GONE. KEEP CONTAINERS CLOSED WHEN NOT IN USE. USE WITH ADEQUATE VENTILATION. STORE IN COOL PLACE. KEEP AWAY FROM HEAT AND OPEN FLAME. KEEP OUT OF REACH OF CHILDREN.

## OTHER PRECAUTIONS

USE EXPLOSION-PROOF VENTILATION AS REQUIRED TO CONTROL VAPOR CONCENTRATIONS. AIR DRY CONTAMINATED CLOTHING IN WELL VENTILATED AREA. THEN LAUNDER BEFORE REUSING.

## 

## RESPIRATORY PROTECTION

WEAR APPROVED RESPIRATORY PROTECTION SUCH AS A NIOSH/MSHA APPROVED ORGANIC VAPOR CARTRIDGE RESPIRATOR OR AN AIR-SUPPLYING RESPIRATOR UNLESS VENTILATION EQUIPMENT IS ADEQUATE TO KEEP AIRBORNE CONCENTRATIONS BELOW THE RECOMMENDED TIME WEIGHTED EXPOSURE LIMITS.

#### VENTILATION

GENERAL MECHANICAL VENTILATION OR LOCAL EXHAUST SHOULD BE SUITABLE TO KEEP VAPOR CONCENTRATIONS BELOW TLV. VENTILATION EQUIPMENT MUST BE EXPLOSION PROOF.

## PROTECTIVE GLOVES

IMPERMEABLE CHEMICAL HANDLING GLOVES FOR SKIN PROTECTION.

## EYE PROTECTION

USE CHEMICAL SAFETY GLASSES, GOGGLES, OR FACESHIELDS FOR EYE PROTECTION.

#### OTHER PROTECTIVE CLOTHING OR EQUIPMENT

USE IMPERMEABLE APRONS AND PROTECTIVE CLOTHING WHENEVER POSSIBLE TO PREVENT SKIN CONTACT. THE USE OF HEAD CAPS WHEN SPRAYING IS STRONGLY RECOMMENDED.

308-JEL'D STAIN 550-HERITAGE OAK

Page: 4

## WORK/HYGIENIC PRACTICES

WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING, OR USING RESTROOMS. EYE WASH STATION AND SAFETY SHOWER IN THE WORKPLACE ARE RECOMMENDED.

#### 

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA AVAILABLE TO US AND IS BELIEVED TO BE CORRECT. WOOD KOTE PRODUCTS MAKES NO WARRANTY, EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. WOOD KOTE PRODUCTS ASSUMES NO RESPONSIBILITY FOR INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN.