SAFETY DATA SHEET

WOOD KOTE PRODUCTS INC.

www.woodkote.com

Section 1: Product and Company Identification

Product Name: C-U-2 (Glass Cleaner) Product Code: 6000

TEL: 503-285-8371

WOOD KOTE PRODUCTS INC. 800-843-7666 (Toll Free USA & Canada)

8000 NE 14th Place FAX: 503-285-8374

Portland, Oregon 97211 E-MAIL: info@woodkote.com

USA

EMERGENCY CONTACT

INFOTRAC (Transportation): 800-535-5053

Product Use: Glass Cleaner. This product is intended for professional use and application only.

Section 2: Hazards Identification

GHS Ratings:

Eye corrosive 2B Mild eye irritant: subcategory 2B. Reversible in 7 days.

GHS Hazards

H320 Causes eye irritation.

GHS Precautions

P264 Wash skin thoroughly after handling.

P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact

lenses if present and easy to do – continue rinsing

P337+P313 If eye irritation persists, get medical advice/attention

P501WK If spilled, contain spilled material and dispose of contaminated absorbent, container

and unused contents in accordance with local, state and federal regulations. Avoid

release to the environment.

Section 3: Composition / Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Water	7732-18-5	72.00%
Isopropyl Alcohol	67-63-0	25.00%
Dipropylene Glycol Methyl Ether	34590-94-8	2.00%

Section 4: First Aid Measures

IF INHALED: Move to fresh air. Call a physician if symptoms develop or persist.

IF IN EYES: Direct contact with eyes may cause temporary irritation.

IF ON SKIN: Gently wash with plenty of soap and water. **IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting.

Note to Physician: Provide general supportive measures and treat symptomatically.

Section 5: Fire Fighting Measures

Flash Point: 95 C (203 F)

LEL: 2.00 UEL: 13.00

EXTINGUISHING MEDIA: Use water fog, foam, dry chemical, or CO2.

No unusual fire or explosion hazards noted. Container may melt and leak in heat of fire.

Use standard fire fighting procedures and consider the hazards of other involved materials.

SDS for: 6000 Page 1 of 3

Section 6: Accidental Release Measures

PERSONAL PRECAUTIONS: Wash thoroughly after handling.

ENVIRONMENTAL PRECAUTIONS: Outside of normal use, avoid release to the environment.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP: Dike large spills. Clean residue from spill site.

Section 7: Handling and Storage

HANDLING: Do not taste or swallow. Avoid contact with eyes and skin. Wash thoroughly after handling **STORAGE:** Keep in original container tightly closed when not in use and stored away in a cool dark area.

COMMENTS: Read label before use. KEEP OUT OF REACH OF CHILDREN!

Section 8: Exposure Control and Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Water 7732-18-5	NDA	NDA	NDA
Isopropyl Alcohol 67-63-0	TWA 400 ppm 980 mg/m3	TWA 200 ppm STEL 400 ppm	NIOSH: TWA 400 ppm 980 mg/m3
Dipropylene Glycol Methyl Ether 34590-94-8	TWA 100 ppm 600 mg/m3	TWA 100 ppm STEL 150 ppm	NIOSH: TWA 100 ppm 600 mg/m3

VENTILATION: Good general ventilation should be used. Ventilation rates should be matched to conditions.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Maintain eye wash fountain and quick drench facilities in work areas.

SKIN: For prolonged or repeated skin contact use suitable protective gloves.

RESPIRATORY: Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or symptoms are

experienced.

WORK HYGIENIC PRACTICES: Handle in accordance with good industrial hygiene and safety practice. Wash

thoroughly with soap and water after handling and before eating, drinking, or using tobacco.

OTHER USE PRECAUTIONS: Use with adequate ventilation. Do not get in eyes and skin. Wash thoroughly after

handling.

Section 9: Physical and Chemical Properties

Appearance: Transparent Green Odor: Citrus

Viscosity: N/A Solubility in Water: Complete

PH Essentially Neutral. Autoignition temperature: 399°C

Decomposition temperature: N/A Vapor Pressure: 4.4 hPa at 25 C

Vapor Density: 2.1 Melting point: N/A
Freezing point: N/A Boiling range: 82°C

Flash point: 203 F,95 C Evaporation rate: Slower than Ether

Page 2 of 3

Specific Gravity (SG) 0.940 VOC g/L (Material) 253.4

Section 10: Stability and Reactivity

VOC g/L (Coating) 767.7

Stability:

Under normal conditions:

STABLE

Incompatibilities:

NDA

Hazardous decomposition:

Hazardous polymerization will not occur.

SDS for: 6000

Section 11: Toxicological Information

Component Toxicity

67-63-0 Isopropyl Alcohol

Oral LD50: 3,600 mg/kg (Mouse)

PRIMARY ROUTES OF ENTRY

NDA

Section 12: Ecological Information

ENVIRONMENTAL SUMMARY: Avoid uncontrolled releases of this material. Where spills are possible, comprehensive spill response plan should be developed and implemented. Do not contaminate water when cleaning equipment or disposing of equipment washwaters or rinsate.

Component Ecotoxicity

Isopropyl Alcohol

(LC50): 100000 mg/l 96 hours [Fathead Minnow]. 64000 mg/l 96 hours [Fathead

Minnow]

Section 13: Disposal Considerations

DISPOSAL: If spilled, contain spilled material and dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Avoid release to the environment.

Section 14: Transport Information

Agency Proper Shipping Name NDA

UN Number

Packing Group

Hazard Class

Section 15: Regulatory Information

ACGIH (American Conference of Governmental Industrial Hygienists)

TWA (Time-Weighted Average)

OSHA (Occupational Safety and Health Administration)

NIOSH (National Institute for Occupational Safety and Health)

Section 16: Other Information


ABBREVIATIONS USED IN THE SDS:

NDA: No Data Available

Hazardous Material Information System (HMIS)

National Fire Protection Association (NFPA)





DISCLAIMER: The information contained herein is based on data available to us and is believed to be correct. WOOD KOTE PRODUCTS makes no warranty, expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable. WOOD KOTE PRODUCTS assumes no responsibility for injury from the use of the product described herein. The conditions or methods of handling, storage, use, and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with handling, storage, use or disposal of the product.

Date Revised: 6/16/2016

SDS for: 6000 Page 3 of 3