



1. Product Name

AlkoThin

2. Manufacturer

WOOD KOTE PRODUCTS INC
8000 NE 14th PI (97211)
PO Box 17192
Portland OR 97217
Tel: (800) 843-7666 (USA & Canada)
Tel: (503) 285-8371
Fax: (503) 285-8374
info@woodkote.com
www.woodkote.com

3. Product Description

BASIC USE

AlkoThin is intended for professional use only. It is a methanol solvent used to reduce certain alcohol coatings where local regulations allow. It is recommended for general cleaning to remove stain from non-porous surfaces and from application equipment.

ADVANTAGES

- Consistent formulation
- Wide variety of uses
- Economical

COMPOSITION & PROPERTIES

AlkoThin is made from methyl alcohol.

TYPES

AlkoThin is available from the factory in one formulation.

SIZES

AlkoThin is sold in 1-Gal (3.8L) HDPE plastic containers, 5-Gal (19L) and 55-Gal (208.5L) metal containers.

4. Technical Data

PHYSICAL PROPERTIES

See table 1

5. Installation

AlkoThin can be used as a diluent in alcohol based coatings and will accelerate their dry time. Under normal conditions, the amount of AlkoThin should not exceed 10% of the undiluted product.

PRECAUTIONS

AlkoThin is flammable. Therefore, be certain that on-site conditions allow for adequate ventilation and pose no threat of fire or other health hazards. CAUTION: AlkoThin is a high VOC solvent. It is intended to be used as an additive or cleaning solvent only where regulations allow. AlkoThin should only be used by qualified professionals who have read and understood this information. Before using any chemical, read its label and Material Safety Data Sheet (MSDS).

CLEAN UP

If spilled, clean surfaces using an absorbent cloth. Any cloth containing AlkoThin should be left unfolded to dry in open air before disposal.

6. Availability & Cost

AVAILABILITY

AlkoThin is available through recognized Wood Kote retailers or directly from the manufacturer. A list of stocking dealers is available from the manufacturer and can be found on the manufacturer's web site.

COST

Cost information is available from recognized Wood Kote retailers or from the manufacturer.

7. Warranty

AlkoThin is sold without warranty except that Wood Kote guarantees that the product is manufactured within the specifications provided herein. Unless Wood Kote warranties, in writing, specific products on an identified project, Wood Kote's liability is limited to the replacement cost of the product. The information provided herein is accurate to the best of Wood Kote's knowledge or obtained by Wood Kote from sources believed by Wood Kote to be accurate. Wood Kote



Products Inc does not assume any legal responsibility for use or reliance upon this information.

8. Maintenance

STORAGE

Keep in the original containers tightly closed when not in use and stored away from direct light at temperatures between 32-110°F (0-43°C).

DISPOSAL

Dispose of only in accordance with local, state and federal regulations.

9. Technical Services

Additional information is available directly from the manufacturer and from the manufacturer's web site.

10. Filing Systems

- Wood Kote—Product Catalog
- Additional product information is available from the manufacturer.
- www.woodkote.com



Physical Properties Table 1

Mfr No	APPEARANCE	VOC gm/L	FLASH PT
4530	Clear	787	45°F (7.2°C)

This page intentionally left blank.

