



1. Product Name

WashThin

2. Manufacturer

WOOD KOTE PRODUCTS INC
8000 NE 14th PI (97211)
PO Box 17192
Portland OR 97217
Tel: (800) 843-7666 (USA & Canada)
Tel: (503) 285-8371
Fax: (503) 285-8374
info@woodkote.com
www.woodkote.com

3. Product Description

BASIC USE

WashThin is intended for professional use only. It is an economical and aggressive general-purpose solvent used to clean acetate and nitrocellulose-based products from tools and equipment. WashThin can also be used to clean a wide variety of other products from surfaces such as printing presses and silk-screening equipment. WashThin is a cleaning solvent and not a coating, and thus it is not subject to the US Environmental Protection Agency (EPA) Volatile Organic Compound (VOC) emission requirements for Architectural and Industrial Maintenance (AIM) coatings (effective 13Sep99).

ADVANTAGES

- Consistent formulation
- Economical
- Wide variety of uses

COMPOSITION & PROPERTIES

WashThin is a blend of ketones and aliphatic solvents.

TYPES

WashThin is available from the factory in one formulation.

SIZES

WashThin is sold in 1-Gal (3,8L), 5-Gal (19L) and 55-Gal (208,5L) metal containers.

4. Technical Data

PHYSICAL PROPERTIES

See table 1

5. Installation

WashThin is intended to be used as a cleaning solvent only where regulations allow.

PRECAUTIONS

WashThin is extremely flammable. Therefore, be certain that on-site conditions allow for adequate ventilation and pose no threat of fire or other health hazards. WashThin should only be used by qualified professionals who have read and understood this information. Before using any chemical, read its label and Material Safety Data Sheet (MSDS).

CLEAN UP

If spilled, clean surfaces using an absorbent cloth. Any cloth containing WashThin should be left unfolded to dry in open air before disposal.

6. Availability & Cost

AVAILABILITY

WashThin is available through recognized Wood Kote retailers or directly from the manufacturer. A list of stocking dealers is available from the manufacturer and can be found on the manufacturer's web site.

COST

Cost information is available from recognized Wood Kote retailers or from the manufacturer.

7. Warranty

WashThin is sold without warranty except that Wood Kote guarantees that the product is manufactured within the specifications provided herein. Unless Wood Kote warranties, in writing, specific products on an identified project, Wood Kote's liability is limited to the replacement cost of the product. The information provided herein is accurate to the best of Wood Kote's



knowledge or obtained by Wood Kote from sources believed by Wood Kote to be accurate. Wood Kote Products Inc does not assume any legal responsibility for use or reliance upon this information.

8. Maintenance

STORAGE

Keep in the original containers tightly closed when not in use and stored away from direct light at temperatures between 32-110°F (0-43°C).

DISPOSAL

Dispose of only in accordance with local, state and federal regulations.

9. Technical Services

Additional information is available directly from the manufacturer and from the manufacturer's web site.

10. Filing Systems

- Wood Kote-Product Catalog
- Additional product information is available from the manufacturer.
- www.woodkote.com



Physical Properties Table 1

Mfr No	APPEARANCE	VOC gm/L	FLASH PT
4540	Clear	857	23°F (-5°C)

WashThin

This page intentionally left blank.

SO