



1. Product Name

LaqAdd

2. Manufacturer

WOOD KOTE PRODUCTS INC
8000 NE 14th PI (97211)
PO Box 17192
Portland OR 97217
Tel: (800) 843-7666 (USA & Canada)
Tel: (503) 285-8371
Fax: (503) 285-8374
info@woodkote.com
www.woodkote.com

3. Product Description

BASIC USE

LaqAdd is intended for professional use only. It is an additive formulated to control the evaporation rate, flow, application and the final appearance of lacquer-based coatings. LaqAdd is recommended for use in Wood Kote nitrocellulose-based lacquers when high temperature and/or humidity are a factor. LaqAdd is an additive and not a coating, and thus it is not subject to the US Environmental Protection Agency (EPA) Volatile Organic Compound (VOC) emission requirements for Architectural and Industrial Maintenance coatings (effective 13Sep99).

ADVANTAGES

- Consistent formulation
- Convenient
- Versatile

COMPOSITION & PROPERTIES

LaqAdd is made from ethylene glycol n-butyl ether.

TYPES

LaqAdd is available from the factory in one formulation.

SIZES

LaqAdd is sold in 1-Gal (3,8L), 5-Gal (19L) and 55-Gal (208,5L) metal

containers.

4. Technical Data

PHYSICAL PROPERTIES

See table 1

5. Installation

LaqAdd is intended to be used as an additive only. LaqAdd should be thoroughly dispersed into lacquer using an electric mixer or mechanical agitation for no less than 2 minutes. Under normal conditions 2-4 fl oz/gal (15,5-31 ml/L) should be sufficient.

PRECAUTIONS

Additional product may be required when temperature and humidity are extremely high. DO NOT exceed 32 fl oz/gal (248,9 ml/L). LaqAdd should only be used by qualified professionals who have read and understood this information. Before using any chemical, read its label and Material Safety Data Sheet (MSDS).

CLEAN UP

If spilled, clean surfaces using an absorbent cloth. Any cloth containing LaqAdd should be left unfolded to dry in open air before disposal.

6. Availability & Cost

AVAILABILITY

LaqAdd is available through recognized Wood Kote retailers or directly from the manufacturer. A list of stocking dealers is available from the manufacturer and can be found on the manufacturer's web site.

COST

Cost information is available from recognized Wood Kote retailers or from the manufacturer.

7. Warranty

LaqAdd is sold without warranty except that Wood Kote guarantees that the product is manufactured within the specifications provided herein. Unless Wood Kote warranties, in writing, specific products on an identified project, Wood Kote's liability is limited to the



LaqAdd

replacement cost of the product. The information provided herein is accurate to the best of Wood Kote's knowledge or obtained by Wood Kote from sources believed by Wood Kote to be accurate. Wood Kote Products Inc does not assume any legal responsibility for use or reliance upon this information.

8. Maintenance

STORAGE

Keep in the original containers tightly closed when not in use and stored away from direct light at temperatures between 32-110°F (0-43°C).

DISPOSAL

Dispose of only in accordance with local, state and federal regulations.

9. Technical Services

Additional information is available directly from the manufacturer and from the manufacturer's web site.

A

Physical Properties Table 1

Mfr No	APPEARANCE	VOC gm/L	FLASH PT
606	Translucent White	Exempt (900)	150°F (65,5°C)

This page intentionally left blank.

A